

| FNGINE | |
|--------|---|
| | • |

| Horsepower | 130 hp (97 kW) |
|------------------|-----------------|
| Fuel Capacity | 46 gal (174 l) |
| Gallons Per Hour | 2 gph (7.6 lph) |

WEIGHT AND MEASUREMENTS

| Ground Pressure | 4.12 psi (0.29 kg/cm²) |
|------------------|------------------------|
| Weight | 26,680 lbs (12,102 kg) |
| Total Length | 498 in (12,649 mm) |
| Width | 96 in (2,438 mm) |
| Height | 138 in (3,505 mm) |
| Ground Clearance | 17.2 in (437 mm) |

TRACK SPECIFICATIONS


| Track Ground A | Area | 6,480 in² (164,592 mm²) |
|----------------|---------|------------------------------|
| Track Width | | 27.6 in (701 mm) |
| Track Type | Metal-l | Embedded Rubber Track (MERT) |

OPERATIONAL CAPABILITIES

| Cutting Height | 75 ft (22.9 m) |
|--------------------|----------------------|
| Saw Blade Diameter | 24 in (610 mm) |
| Saw Head | 180-degree rotation |
| Operator Cab | ROPS, FOPS Certified |

PROVEN RUBBER TRACK SYSTEM

Introducing the new Jarraff Rubber Track. This innovative machine offers all of the same high-quality trimming functionality that customers have come to expect from Jarraff, but now comes equipped with rubber tracks. With its proven rubber track system, it offers excellent flotation in wet ground while still allowing for roading of the machine.



1731 GAULT STREET, ST. PETER, MN 56082 JARRAFF.COM | 800-767-7112

