







Light weight

Structural layout of the machine allows a highly weight optimized structure.



Flexible mounting on various carrier vehicles

The S700e/s can be mounted to all possible carrier vehicles using the universal mounting plate or the mounting frame for skid steer loaders.



Plug & Mulch

No extra drain line is required. Freewheel and pressure protection are already integrated into the motor.



Support

Thanks to a special developed support, the transport of the S700e/s is quick and easy.

	EXCAVATOR MOUNTING	SKID-STEER LOADER MOUNTING
Grid wheel width in [mm]	4.48 [114]	4.48 [114]
Grid wheel diameter in [mm]	27.6 [700]	27.6 [700]
Power range	6-12t	up to 120 HP
Volume flow gpm [l/min]	16-37 [60-140]	16-37 [60-140]
Weight lbs [kg]*	644 [292]	860 [390] (incl. mounting frame)
Tools	45	45







- + Durable cutting teeth
- + Highest carbide grade made in Germany
- + Quick change system
- + Heavy duty disk
- + Dual-direction cutting with teeth on both sides of the disk
- + High grinding productivity



Grinding disk

The grinding disk of the S700e/s has about five tool elements and five wear resistant elements, which are mounted alternating one after another.



Other sales and service sites can be found on www.prinoth.com

PRINOTH GmbH Im Branden 15 88634 Herdwangen GERMANY Phone +49 7557 9212 0 prinoth.germany@prinoth.com

Brennerstraße 34 39049 Sterzing (BZ) ITALY Phone +39 0472 72 26 22 prinoth@prinoth.com

PRINOTH AG

PRINOTH Ltd. 1001 J.-A. Bombardier Street Granby Qc J2J 1E9 CANADA Phone +1 450 776 3600 sales.na@prinoth.com